

COMMA - SX 75W90 GL5

Page: 1

Compilation date: 14/02/2014

Revision No: 14

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: COMMA - SX 75W90 GL5

Product code: SX*L

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Automotive gear oil.

1.3. Details of the supplier of the safety data sheet

Company name: Comma Oil & Chemicals Ltd.

Dering Way Gravesend

Kent

DA12 2QX

Tel: +44 01474 564311 **Fax:** +44 01474 333000

Email: sales@commaoil.com

1.4. Emergency telephone number

Emergency tel: +44 01474 564311

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: -: EUH208

Classification under CHIP: This product has no classification under CHIP.

2.2. Label elements

Label elements under CLP:

Hazard statements: EUH208: Contains long chain alkyl amine. May produce an allergic reaction.

Label elements under CHIP:

Hazard symbols: No significant hazard.

Precautionary phrases: Contains long chain alkyl amine. May produce an allergic reaction.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

COMMA - SX 75W90 GL5

Page: 2

Hazardous ingredients:

LUBRICATING OIL (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED - REACH registered number(s): 01-2119474878-16

EINECS	CAS	CHIP Classification	CLP Classification	Percent
276-737-9	72623-86-0	Xn: R65 Substance with a Community workplace exposure limit.	Asp. Tox. 1: H304	10-30%

LONG CHAIN ALKYL AMINE

-	Proprietary	T: R23/24; Xn: R22; Xn: R48/20; C:	Acute Tox. 3: H311; Skin Sens. 1:	<1%
		R34; Sens.: R43; N: R50/53	H317; Aquatic Acute 1: H400; Aquatic	
			Chronic 1: H410; Acute Tox. 2: H330;	
			Acute Tox. 4: H302	

LONG CHAIN ALKENYL AMINE #1

-	Proprietary	Xn: R22; C: R35; N: R50	Acute Tox. 4: H302; Skin Corr. 1A:	<1%
			H314; Aquatic Acute 1: H400	

Contains: Hazardous ingredients present at or above regulatory disclosure limits.

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

COMMA - SX 75W90 GL5

Page: 3

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3 for oil mist	-	-	-

Hazardous ingredients:

LUBRICATING OIL (PETROLEUM), C15-30, HYDROTREATED NEUTRAL OIL-BASED

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
Olale	U IIOUI I VVA	I I I I I I I I I I I I I I I I I I I	U IIOUI I VVA	I I I I I I I I I I I I I I I I I I I

COMMA - SX 75W90 GL5

Page: 4

EU 5 mg/m3 - - - -

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid Colour: Straw

Odour: Characteristic odour

Evaporation rate: Negligible Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: 90 mm2/s @ 40 C

Flash point °C: > 200 Relative density: 0.86 @ 20 C

pH: n/a

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

COMMA - SX 75W90 GL5

Page: 5

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Non-volatile. Floats on water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste code number: 13 02 06

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

COMMA - SX 75W90 GL5

Page: 6

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: --

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No

1272/2008.

Phrases used in s.2 and s.3: EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H311: Toxic in contact with skin.

H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H330: Fatal if inhaled.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

R22: Harmful if swallowed.

R23/24: Toxic by inhalation and in contact with skin.

R34: Causes burns.

R35: Causes severe burns.

R43: May cause sensitisation by skin contact.

R48/20: Harmful: danger of serious damage to health by prolonged exposure through

inhalation.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

R50: Very toxic to aquatic organisms.

R65: Harmful: may cause lung damage if swallowed.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

COMMA - SX 75W90 GL5

Page: 7

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = occular

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. - - -