# SAFETY DATA SHEET



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Hylomar Exhaust Repair Putty ERP5

of the mixture

Registration number

**Synonyms** None. SDS number 36

legue date 04-July-2013

Version number 01 **Revision date** Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Exhaust putty.

Uses advised against Use in accordance with supplier's recommendations.

1.3. Details of the supplier of the safety data sheet

Hylomar Ltd. Manufacturer:

Address: Hylo House, Cale Lane, New Springs,

Wigan, Greater Manchester,

UK, WN2 1JT

Telephone number: +44(0)1942 617000 E-mail address: info@hylomar.co.uk Contact person: **Technical Department** 1-760-476-3961 1.4. Emergency telephone

number

Access code: 333544

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

Classification Xi:R36/38

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

**Health hazards** 

H315 - Causes skin irritation. Skin corrosion/irritation Category 2 H319 - Causes serious eye Serious eye damage/eye irritation Category 2

irritation.

**Hazard summary** 

Physical hazards Not classified for physical hazards.

**Health hazards** Irritating to eyes and skin. Occupational exposure to the substance or mixture may cause adverse

health effects.

**Environmental hazards** Not classified for hazards to the environment.

Specific hazards Irritating to eyes and skin.

Main symptoms Irritation of eyes and mucous membranes. Exposed may experience eye tearing, redness, and

discomfort. Skin irritation. May cause redness and pain.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Silicic acid, sodium salt

Hylomar Exhaust Repair Putty ERP5 SDS EU

#### **Hazard pictograms**



Signal word Warning

**Hazard statements** H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

**Precautionary statements** 

Prevention P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P264 - Wash thoroughly after handling.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove Response

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention. P302 + P352 - IF ON SKIN: Wash with plenty of soap and water. P332 + P313 - If skin irritation occurs: Get medical advice/attention. P362 - Take off contaminated clothing and wash before reuse.

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. Disposal

Supplemental label information Not applicable. 2.3. Other hazards Not assigned.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **General information**

CAS-No. / EC No. REACH Registration No. Chemical name % **Notes** 

Silicic acid, sodium salt 10 - 30 1344-09-8

215-687-4

Classification: **DSD:** Xi;R36/37/38

> Skin Irrit. 2;H315, Eye Irrit. 2;H319, STOT SE 3;H335 CLP:

CLP: Regulation No. 1272/2008. DSD: Directive 67/548/EEC.

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments The full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent by

weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# **SECTION 4: First aid measures**

General information If you feel unwell, seek medical advice (show the label where possible). Ensure that medical

personnel are aware of the material(s) involved, and take precautions to protect themselves. Show

this safety data sheet to the doctor in attendance.

4.1. Description of first aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact Immediately take off all contaminated clothing. Wash off immediately with soap and plenty of

water. Get medical attention if irritation develops and persists. Wash contaminated clothing before

Eye contact Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses, if present

and easy to do. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Drink a few glasses of water or milk. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and

delayed

Irritation of eyes and mucous membranes. Exposed may experience eye tearing, redness, and

discomfort. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically.

# **SECTION 5: Firefighting measures**

General fire hazards The product is not flammable.

Hylomar Exhaust Repair Putty ERP5 SDS EU 2 / 10

5.1. Extinguishing media

Suitable extinguishing

media

Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture By heating and fire, toxic vapours/gases may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in

the workplace.

Special fire fighting

procedures

Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Prevent runoff from fire control or dilution from entering streams, sewers or drinking water supply.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this SDS. In case of spills, beware of slippery floors and surfaces.

personnel

Keep unnecessary personnel away. Wear protective clothing as described in Section 8 of this

safety data sheet.

6.2. Environmental precautions

For emergency responders

Prevent further leakage or spillage if safe to do so. Do not discharge into drains, water courses or

onto the ground.

6.3. Methods and material for containment and cleaning up Scrape up the spilled material. Transfer to a container for disposal. Following product recovery,

flush area with water.

6.4. Reference to other

sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## **SECTION 7: Handling and storage**

7.1. Precautions for safe

handling

Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this safety data sheet. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe

good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, spark, open flames and other sources of ignition. Keep container tightly closed in a cool, well-ventilated place. Store away from incompatible materials. Incompatible materials: Fluorine. Fluorides.

7.3. Specific end use(s)

Exhaust putty.

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

## Occupational exposure limits

#### Austria. MAK List

Components	Туре	Value	Form	
Silicon dioxide (CAS	MAK	4 mg/m3	Inhalable fraction.	_
7631-86-9)				

# Belgium. Exposure Limit Values.

Components	Туре	Value	Form	
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	Mist.	
Silicon dioxide (CAS 7631-86-9)	TWA	10 mg/m3		

#### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Туре	Value	Form
Kaolinite (CAS 1318-74-7)	TWA	2 mg/m3	
Silicon dioxide (CAS 7631-86-9)	TWA	10 mg/m3	Inhalable fraction.
•		0,07 mg/m3	Respirable fraction.

## Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Туре	Value	
Silicon dioxide (CAS 7631-86-9)	TWA	2 mg/m3	

Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	Ceiling	15 mg/m3	Mist.
	TWA	10 mg/m3	Mist.
Silicon dioxide (CAS 7631-86-9)	TWA	4 mg/m3	Dust.
Estonia. OELs. Occupational Expo 2001)	osure Limits of Hazardous Sub	ostances. (Annex of Regulati	on No. 293 of 18 Septemi
Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	
Kaolinite (CAS 1318-74-7)	TWA	2 mg/m3	
Silicon dioxide (CAS 7631-86-9)	TWA	2 mg/m3	Respirable dust.
Finland. Workplace Exposure Lim	its		
Components	Type Value		
Glycerin (CAS 56-81-5)	TWA	20 mg/m3	
Kaolinite (CAS 1318-74-7)	TWA	2 mg/m3	
France. Threshold Limit Values (V	LEP) for Occupational Exposu	•	NRS ED 984
Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	VME	10 mg/m3	Aerosol
Germany. DFG MAK List (advisory in the Work Area (DFG)	/ OELs). Commission for the I	nvestigation of Health Hazar	ds of Chemical Compour
Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	TWA	50 mg/m3	Inhalable fraction.
Germany. TRGS 900, Limit Values		· ·	
Components	Туре	Value	Form
Silicon dioxide (CAS 7631-86-9)	AGW	4 mg/m3	Inhalable fraction.
Greece. OELs (Decree No. 90/1999	), as amended)		
Components	Туре	Value	
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	
Iceland. OELs. Regulation 154/199		· ·	
Components	Туре	Value	
Kaolinite (CAS 1318-74-7)	TWA	2 mg/m3	
Ireland. Occupational Exposure L		= ···· <del>g</del> ····· <del>c</del>	
Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	Mist.
Silicon dioxide (CAS	TWA	6 mg/m3	Total inhalable dust.
7631-86-9)		2,4 mg/m3	Respirable dust.
Italy. OELs		۵, <del>۰</del> ۱۱۱۹/۱۱۱۵	r tespirable dust.
Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	Mist.
Kaolinite (CAS 1318-74-7)	TWA	1 mg/m3	Respirable fraction.
Latvia. OELs. Occupational expos		•	
Components	Туре	Value	
Silicon dioxide (CAS 7631-86-9)	TWA	1 mg/m3	
7031-80-9) Lithuania. OELs. Limit Values for	Chemical Substances. Genera	al Requirements (Hvaiene No	orm HN 23:2007)
Components	Type	Value	<b>,</b>
- ompononta	· Ahe	vaiut	
Kaolinite (CAS 1318-74-7)	TWA	1 mg/m3	

Hylomar Exhaust Repair Putty ERP5 SDS EU

Components	Туре	Value	Form
Silicon dioxide (CAS 7631-86-9)	TLV	1,5 mg/m3	Respirable dust.
Poland. MACs. Minister of Labou Working Environment	r and Social Policy Regarding	Maximum Allowable Concent	rations and Intensities
Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	Aerosol
Silicon dioxide (CAS 7631-86-9)	TWA	2 mg/m3	Respirable dust.
,		10 mg/m3	Total dust.
Portugal. VLEs. Norm on occupa	tional exposure to chemical ac	gents (NP 1796)	
Components	Туре	Value	
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	
agents	_		
Components	Type	Value	
•	Type TWA	Value 10 mg/m3	
Components Glycerin (CAS 56-81-5) Silicon dioxide (CAS 7631-86-9)	T <b>ype</b> TWA TWA	<b>Value</b> 10 mg/m3 0,3 mg/m3	
Glycerin (CAS 56-81-5) Silicon dioxide (CAS 7631-86-9) Slovenia. OELs. Regulations con	TWA TWA	10 mg/m3 0,3 mg/m3	to chemicals while w
Glycerin (CAS 56-81-5) Silicon dioxide (CAS 7631-86-9) Slovenia. OELs. Regulations conf	TWA TWA	10 mg/m3 0,3 mg/m3	to chemicals while w
Glycerin (CAS 56-81-5) Silicon dioxide (CAS 7631-86-9) Slovenia. OELs. Regulations con (Official Gazette of the Republic of Components Silicon dioxide (CAS	TWA TWA cerning protection of workers of Slovenia)	10 mg/m3 0,3 mg/m3 against risks due to exposure	
Glycerin (CAS 56-81-5) Glicon dioxide (CAS 7631-86-9) Glovenia. OELs. Regulations concomposition of the Republic of Components Glicon dioxide (CAS 7631-86-9)	TWA TWA  cerning protection of workers of Slovenia)  Type  TWA	10 mg/m3 0,3 mg/m3 against risks due to exposure Value	Form
Glycerin (CAS 56-81-5) Glicon dioxide (CAS 7631-86-9) Glovenia. OELs. Regulations cond Official Gazette of the Republic of Components Glicon dioxide (CAS 7631-86-9) Gpain. Occupational Exposure Lie	TWA TWA  cerning protection of workers of Slovenia)  Type  TWA	10 mg/m3 0,3 mg/m3 against risks due to exposure Value	Form
Glycerin (CAS 56-81-5) Silicon dioxide (CAS 7631-86-9) Slovenia. OELs. Regulations concomponents Silicon dioxide (CAS 7631-86-9) Spain. Occupational Exposure Line Components	TWA TWA  cerning protection of workers of Slovenia)  Type  TWA  TWA	10 mg/m3 0,3 mg/m3 against risks due to exposure Value 4 mg/m3	Form Inhalable fraction.
Glycerin (CAS 56-81-5) Gilicon dioxide (CAS 7631-86-9) Glovenia. OELs. Regulations cond Official Gazette of the Republic of Components Gilicon dioxide (CAS 7631-86-9) Gpain. Occupational Exposure Lieus Components Glycerin (CAS 56-81-5)	TWA TWA  Cerning protection of workers of Slovenia)  Type TWA  mits  Type  TWA	10 mg/m3 0,3 mg/m3 against risks due to exposure Value 4 mg/m3	Form Inhalable fraction. Form
Glycerin (CAS 56-81-5) Glicon dioxide (CAS 7631-86-9) Glovenia. OELs. Regulations condition of the Republic of Components Glicon dioxide (CAS 7631-86-9) Gpain. Occupational Exposure Line Components Glycerin (CAS 56-81-5) Gweden. Occupational Exposure Components	TWA TWA  Cerning protection of workers of Slovenia)  Type TWA  mits  Type  TWA	10 mg/m3 0,3 mg/m3 against risks due to exposure Value 4 mg/m3	Form Inhalable fraction. Form
Glycerin (CAS 56-81-5) Glicon dioxide (CAS 7631-86-9) Glovenia. OELs. Regulations condofficial Gazette of the Republic of Components Glicon dioxide (CAS 7631-86-9) Gpain. Occupational Exposure Lie Components Glycerin (CAS 56-81-5) Gweden. Occupational Exposure Components	TWA TWA  Cerning protection of workers of Slovenia)  Type TWA  mits  Type TWA  Limit Values	10 mg/m3 0,3 mg/m3  against risks due to exposure  Value 4 mg/m3  Value  10 mg/m3	Form Inhalable fraction.  Form Mist.
Glycerin (CAS 56-81-5) Gilicon dioxide (CAS 7631-86-9) Glovenia. OELs. Regulations concofficial Gazette of the Republic of Components Gilicon dioxide (CAS 7631-86-9) Gpain. Occupational Exposure Lie Components Glycerin (CAS 56-81-5) Gweden. Occupational Exposure Components Components Caolinite (CAS 1318-74-7)	TWA TWA TWA  cerning protection of workers of Slovenia)  Type TWA  mits  Type TWA  Limit Values Type TWA	10 mg/m3 0,3 mg/m3  against risks due to exposure  Value 4 mg/m3  Value  10 mg/m3  Value	Form Inhalable fraction.  Form Mist.  Form
Glycerin (CAS 56-81-5) Gilicon dioxide (CAS 7631-86-9) Glovenia. OELs. Regulations concofficial Gazette of the Republic of Components Glicon dioxide (CAS 7631-86-9) Gpain. Occupational Exposure Lie Components Glycerin (CAS 56-81-5) Gweden. Occupational Exposure Components Gaolinite (CAS 1318-74-7) Gwitzerland. SUVA Grenzwerte an	TWA TWA TWA  cerning protection of workers of Slovenia)  Type TWA  mits  Type TWA  Limit Values Type TWA	10 mg/m3 0,3 mg/m3  against risks due to exposure  Value 4 mg/m3  Value  10 mg/m3  Value	Form Inhalable fraction.  Form Mist.  Form
Glycerin (CAS 56-81-5)	TWA TWA TWA  cerning protection of workers of Slovenia)  Type TWA  mits  Type TWA  Limit Values Type TWA  Type TWA  Arbeitsplatz	10 mg/m3 0,3 mg/m3  against risks due to exposure  Value 4 mg/m3  Value  10 mg/m3  Value 10 mg/m3	Form Inhalable fraction.  Form Mist.  Form Total dust.

Components	Туре	Value	Form
Glycerin (CAS 56-81-5)	TWA	10 mg/m3	Mist.
Silicon dioxide (CAS 7631-86-9)	TWA	6 mg/m3	Inhalable dust.
,		2.4 mg/m3	Respirable dust.

# **Biological limit values**

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling time
Kaolinite (CAS 1318-74-7)	200	Aluminium	Urine	*
	micrograms/liter			

<sup>\* -</sup> For sampling details, please see the source document.

Hylomar Exhaust Repair Putty ERP5
914433 Version No.: 01 Revision date: - Issue date: 04-July-2013

SDS EU

5 / 10

# Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling time	
Silicon dioxide (CAS 7631-86-9)	25 %	red blood cell or total blood acetylcholinest erase activity (EC. 3.1.1.7.)	Reduction from individual baseline activity in red blood cells	*	

<sup>\* -</sup> For sampling details, please see the source document.

Recommended monitoring

Follow standard monitoring procedures.

procedures

#### Derived no-effect level (DNEL)

Components	Туре	Route	Value	Form
Glycerin (CAS 56-81-5)	Workers	Inhalation	56 mg/m3	Long term exposure systemic effects
Silicic acid, sodium salt (CAS 1344-09-8)	Workers	Dermal	1,59 mg/kg/day	Long term Systemic effects
		Inhalation	5,61 mg/m3	Long term Systemic effects

#### Predicted no effect concentrations (PNECs)

Components	Туре	Route	Value	Form
Glycerin (CAS 56-81-5)	Aqua (freshwater)	Not applicable	0,885 mg/l	
	Aqua (intermittent releases)	Not applicable	8,85 mg/l	
	Aqua (marine water)	Not applicable	0,0885 mg/l	
	Sediment (freshwater)	Not applicable	3,3 mg/kg	
	Sediment (marine water)	Not applicable	0,33 mg/kg	
	Sewage Treatment Plant	Not applicable	1000 mg/l	
	Soil	Not applicable	0,141 mg/kg	
Silicic acid, sodium salt (CAS 1344-09-8)	Aqua (freshwater)	Water	7,5 mg/l	
	Aqua (intermittent releases)	Water	7,5 mg/l	
	Aqua (marine water)	Water	1 mg/l	
	Sewage Treatment Plant	Not applicable	348 mg/l	

#### 8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of

inhalation of vapours.

#### Individual protection measures, such as personal protective equipment

**General information** Personal protective equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear approved safety glasses or goggles.

Skin protection

- Hand protection Wear protective gloves. Nitrile or neoprene gloves are recommended. Be aware that the liquid may

penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the

glove supplier.

- Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection Under normal conditions, respirator is not normally required. In case of inadequate ventilation or

risk of inhalation of dust, use suitable respiratory equipment with particle filter.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

**Environmental exposure** 

controls

Environmental manager must be informed of all major releases.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

**Physical state** Solid **Form** Putty. Colour Dark grey.

Odour No characteristic odor.

Not available. **Odour threshold** pН Not available. Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

Not available. Flash point Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Not available.

Flammability limit - upper

(%)

Not available. Vapour pressure Not available. Vapour density

Not available. Relative density Solubility(ies) Insoluble in water.

**Partition coefficient** (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity Explosive properties** Not available.

Oxidizing properties Not available.

9.2. Other information No relevant additional information available.

## **SECTION 10: Stability and reactivity**

10.1. Reactivity The product is stable and non reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Heat, flames and sparks. 10.5. Incompatible materials Fluorine. Fluorides. 10.6. Hazardous Silicon oxides.

decomposition products

## **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Ingestion Ingestion may cause irritation and malaise.

Inhalation Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

Skin contact Causes skin irritation.

Eve contact Causes serious eye irritation.

Irritation of eyes and mucous membranes. Exposed may experience eye tearing, redness, and **Symptoms** 

discomfort. Skin irritation. May cause redness and pain.

# 11.1. Information on toxicological effects

Hylomar Exhaust Repair Putty ERP5 SDS EU **Acute toxicity** May cause discomfort if swallowed.

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisation Not classified.

Skin sensitisation Not classified.

Germ cell mutagenicity Not classified.

Carcinogenicity Not classified.

Reproductive toxicity Not classified.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not classified.

Mixture versus substance Not applicable.

information

.....

Other information

No other specific acute or chronic health impact noted.

# **SECTION 12: Ecological information**

**12.1. Toxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test results

Silicic acid, sodium salt (CAS 1344-09-8)

Aquatic

Crustacea EC50 Water flea (Ceriodaphnia dubia) 0,28 - 0,57 mg/l, 48 hours
Fish LC50 Western mosquitofish (Gambusia affinis) 1800 mg/l, 96 hours

12.2. Persistence and

degradability

Not available.

12.3. Bioaccumulative potential Not available.
 Bioconcentration factor (BCF) Not available.
 12.4. Mobility in soil Not available.

**Mobility in general** The product is insoluble in water.

12.5. Results of PBT

and vPvB assessment

Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects** None known.

# **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

**EU** waste code

Empty containers should be taken to an approved waste handling site for recycling or disposal.

The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**Disposal methods/information** Do not discharge into drains, water courses or onto the ground. Collect and reclaim or dispose in

sealed containers at licensed waste disposal site. Dispose of contents/container in accordance

with local/regional/national/international regulations.

## **SECTION 14: Transport information**

**ADR** 

Not regulated as dangerous goods.

**RID** 

Not regulated as dangerous goods.

**ADN** 

Not regulated as dangerous goods.

**IATA** 

Not regulated as dangerous goods.

914433 Version No.: 01 Revision date: - Issue date: 04-July-2013 8 / 10

## **IMDG**

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

# **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I

Not listed.

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II

Not listed

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended Not listed.

## Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Silicic acid, sodium salt (CAS 1344-09-8)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work

Not regulated.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding

Not regulated.

#### Other EU regulations

Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances

Not regulated.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work Not listed.

Directive 94/33/EC on the protection of young people at work

Not listed.

**Other regulations**The product is classified and labelled in accordance with EC directives or respective national laws.

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

National regulations 15.2. Chemical safety Follow national regulation for work with chemical agents. No Chemical Safety Assessment has been carried out.

assessment

## **SECTION 16: Other information**

**List of abbreviations** CLP: Regulation No. 1272/2008.

DNEL: Derived No-Effect Level.

PBT: Persistent, bioaccumulative and toxic. PNEC: Predicted No-Effect Concentration. vPvB: Very Persistent and very Bioaccumulative.

Hylomar Exhaust Repair Putty ERP5
914433 Version No.: 01 Revision date: - Issue date: 04-July-2013

References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS) ESIS (European chemical Substances Information System)

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any statements or R-phrases and H-statements under Sections 2 to 15 R36/37/38 Irritating to eyes, respiratory system and skin.

R36/38 Irritating to eyes and skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

**Training information** 

Follow training instructions when handling this material.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently

available.

SDS EU

914433 Version No.: 01 Revision date: - Issue date: 04-July-2013