



SAFETY DATA SHEET POLAR SEAL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name POLAR SEAL
 Product number PLS001
 Internal identification 652/FR/30513

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Water repellent coating for motor vehicles

1.3. Details of the supplier of the safety data sheet

Supplier Autoglym
 Works Road
 Letchworth
 Herts
 SG6 1LU
 UK
 sds@autoglym.com

1.4. Emergency telephone number

Emergency telephone +44 (0) 1462 489498 (24Hrs)

SECTION 2: Hazards identification


2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226
 Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319
 Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.

POLAR SEAL

Precautionary statements	<p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P260 Do not breathe vapours.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</p> <p>P310 Immediately call a POISON CENTER/ doctor.</p> <p>P102 Keep out of reach of children.</p>
Supplementary precautionary statements	<p>P405 Store locked up.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Propan-2-ol		10-30%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R67	
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me		5-10%
CAS number: —		
Classification		
Skin Corr. 1A - H314		
Eye Dam. 1 - H318		
Acetic Acid		1-5%
CAS number: 64-19-7	EC number: 200-580-7	REACH registration number: 01-2119475328-30-XXXX
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 C;R35	
Skin Corr. 1A - H314		
Eye Dam. 1 - H318		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.

POLAR SEAL

Skin contact	Wash skin thoroughly with soap and water or use an approved skin cleanser.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	The product contains organic solvents. Vapours may cause drowsiness and dizziness. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.
Ingestion	May cause discomfort. Nausea, vomiting. Diarrhoea.
Skin contact	Irritating to skin.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Specific treatments	Treat symptomatically.
----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Flammable liquid and vapour. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Carbon dioxide (CO ₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting	Do not use water jet as an extinguisher, as this will spread the fire. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes and clothing. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not allow to enter drainage system, surface or ground water. Prevent material from reaching sewage system, holes and cellars.
----------------------------------	---

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Absorb small quantities with paper towels and evaporate in a safe place. Absorb spillage with non-combustible, absorbent material. No smoking, sparks, flames or other sources of ignition near spillage.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8.
------------------------------------	---

SECTION 7: Handling and storage

POLAR SEAL

7.1. Precautions for safe handling

Usage precautions	For personal protection, see Section 8.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Provide eyewash station. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store at room temperature. Store in accordance with local regulations.
----------------------------	--

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls	Avoid inhalation of vapours.
Eye/face protection	Wear eye protection.
Hand protection	Wear protective gloves. The breakthrough time for any glove material may be different for different glove manufacturers.
Hygiene measures	Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Odour	Pleasant, agreeable.
pH	pH (concentrated solution): 4.72
Melting point	No information available.
Initial boiling point and range	°C @
Flash point	~ 31.6°C Setaflash closed cup.
Evaporation rate	No information available.
Evaporation factor	No information available.
Upper/lower flammability or explosive limits	No information available.
Other flammability	No information available.
Vapour pressure	No information available.

POLAR SEAL

Vapour density	No information available.
Relative density	~ 0.78
Bulk density	No information available.
Solubility(ies)	Completely soluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	No information available.
Oxidising properties	Not available.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Irritation of eyes is assumed.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity Not determined.

12.2. Persistence and degradability

Phototransformation Not determined.

POLAR SEAL

Stability (hydrolysis)	Not determined.
Biodegradation	Expected to be readily biodegradable.
Biological oxygen demand	Not determined.

12.3. Bioaccumulative potential

Partition coefficient	No information available.
------------------------------	---------------------------

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Proper shipping name (IMDG)	FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Proper shipping name (ICAO)	FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Proper shipping name (ADN)	FLAMMABLE LIQUID, N.O.S. (Isopropanol)

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

POLAR SEAL

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	07/03/2018
Revision	1
SDS number	22026
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Signature	Daniel Higgs

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.